Indoor PM from residential coal combustion: levels and chemical composition

E. D. Vicente^{1,2}, A. I. Calvo¹, A. Sánchez de la Campa³, J. de la Rosa³, F. Oduber¹, R. Fraile¹ and C. A. Alves²

¹Department of Physics, University of León, León, 24071, Spain ²Department of Environment and Planning, Centre for Environmental and Marine Studies (CESAM), University of Aveiro, Aveiro, 3810-193, Portugal

³Associate Unit CSIC-University of Huelva "Atmospheric Pollution", Centre for Research in Sustainable Chemistry - CIQSO, University of Huelva, Huelva, E21071, Spain

Keywords: coal combustion, indoor air quality, PM₁₀, PM-bound constituents.

Associated conference topics: 1.6, 4.1, 4.9 Presenting author email: rfral@unileon.es

Coal is still the dominant fuel contributing to the PM_{2.5} disease burden in several countries (McDuffie et al., 2021). Even though the greatest health losses caused by solid fuels combustion were recorded in Eastern and South-eastern Asia and Sub-Saharan Africa (IEA, IRENA, UNSD, World Bank 2022), coal combustion is still used as a source of heating in several European countries (Kerimray et al., 2017). Thus, considering that quantitative estimates of residential coal combustion for indoor air pollution levels in European countries are limited so far, this study intends to assess household PM levels in a household that relies on coal for wintertime heating. Additionally, the chemical characteristics of PM samples will be evaluated.

The combustion experiments were conducted in a detached house without permanent occupation. Indoors, sampling took place in the kitchen/living area (open space), where a small-scale stand-alone stove was installed. Concurrent outdoor measurements were performed. The study consisted of five days of burning, mimicking similar combustion conditions. experiments started by lighting newspaper sheets and wood chips. Afterwards, the stove was fuelled with a new batch of wood chips to raise the temperature in the combustion chamber. Then, a total of 6 batches of mineral coal were burned. Two days of background measurements (without indoor sources) were also performed. The airborne samples were collected using high volume samplers (MCV-CAV) and continuously monitored using real time photometric devices (DustTrak). The chemical composition was obtained by ICP-MS/OES (elements), ion chromatography (watersoluble inorganic ions) and thermal-optical analysis (organic and elemental carbon).

During coal combustion, PM_{10} average concentration indoors ranged from 33.3 to 169 μg m⁻³, which represented increases over background ranging from 1.6 to 8.8 times. The mean I/O PM_{10} ratio was 2.1 ± 1.3 during the coal combustion experiments. From the real time monitoring of particulate mass concentrations indoors, daily fluctuations in the levels and peaks of indoor PM as high as several hundreds of μg m⁻³ were observed. The peaks recorded appeared to result from the refuelling activities. Additionally, the ignition and

stove initial pre-heating generated a high peak in the PM concentrations.

Indoors, OC dominated the carbonaceous component of the sampled particles, accounting on average for 14.5–24.9 wt.% of the total PM $_{10}$ mass, except for the last day of burning, during which EC was the most abundant species (17.7 wt.% of the PM $_{10}$ mass). In general, the I/O ratio was larger than 1 for OC (3.4 \pm 2.9), highlighting the presence of significant indoor sources. Nevertheless, much higher ratios were observed for EC (10.1 \pm 9.2).

The contribution of water-soluble ions to the PM $_{10}$ mass was higher outdoors (27.2 \pm 8.20 %wt.), than indoors during coal combustion (5.90 \pm 3.70 %wt.). Indoors, the most abundant water-soluble ions were SO_4^{2-} and NO_3^- during coal combustion. Major and trace elements represented 4.37 \pm 2.02 wt.% of the PM $_{10}$ mass indoors, while outdoors the average contribution was higher, ranging from 8.04 \pm 0.353 wt.% to 11.7 \pm 3.44 wt.%. The concentration of toxic and carcinogenic species (such as As, Cr, Pb) increased indoors during coal combustion, which is of particular relevance regarding health effects.

This work was partially supported by the Junta de Castilla y Leon co-financed with European FEDER funds (Grant LE025P20) and by the AEROHEALTH project (Ministry of Science and Innovation, co-financed with European FEDER funds, grant PID2019-106164RBI00). This research has also been supported by the RADIATE project under the Grant Agreement 824096 from the EU Research and Innovation programme HORIZON 2020. Furthermore, it is part of the project TED2021-132292B-I00, funded by MCIN/AEI/10.13039/501100011033 and by the European Union "NextGenerationEU"/PRTR.

IEA, IRENA, UNSD, World Bank W (2022) Tracking SDG 7: The Energy Progress Report. Washington DC

Kerimray A, Rojas-solórzano L, Amouei M, et al. (2017) Energy Sustain. Dev. **40**, 19–30.

McDuffie EE, Martin R V., Spadaro J V., et al. (2021) Nat. Commun. **12**, 1–12.